

Fanuc

Wire Guide

| Picture | Code No. | Original P/No. | Dimension | Position | Application |
|---|--------------|--|--|----------|--|
|  | F101 | A290-8021-X763 A290-8021-X764 A290-8021-X765 A290-8021-X766 A290-8021-X767 | Φ0.105 Φ0.155 Φ0.205 Φ0.255 Φ0.305 | Upper | O. P. Q. R. T. W series Manual type Φ22xΦ6xΦ5x28mmL Flush hole Φ0.5 |
|  | F102 | A290-8021-X773 A290-8021-X774 A290-8021-X775 A290-8021-X776 A290-8021-X777 | Φ0.105 Φ0.155 Φ0.205 Φ0.255 Φ0.305 | Lower | O. P. Q. R. T. W series Manual type Φ22xΦ6xΦ5x28mmL Flush hole Φ1.5 |
|  | F103 | A290-8032-X773 A290-8032-X774 A290-8032-X775 A290-8032-X776 A290-8032-X777 | Φ0.105 Φ0.155 Φ0.205 Φ0.255 Φ0.305 | Upper | V. T. W series AWF type Φ22xΦ6xΦ6 x28~31.5mmL Flush hole Φ0.5 |
|  | F104A | A290-8032-X732 A290-8032-X734 A290-8032-X735 A290-8032-X736 A290-8032-X737 | Φ0.105 Φ0.155 Φ0.205 Φ0.255 Φ0.305 | Lower | V. T. W series Simple type for AWF Φ22xΦ8xΦ6 x33.5~34.5mmL |
|  | F104M | A290-8032-X732 A290-8032-X734 A290-8032-X765 A290-8032-X766 A290-8032-X767 | Φ0.105 Φ0.155 Φ0.205 Φ0.255 Φ0.305 | Lower | V. T. W series Manual type for taper 30° Φ22xΦ8xΦ6 x33.5~34.5mmL |
|  | F106 | A290-8011-X831 A290-8011-X833 A290-8011-X834 A290-8011-X865 | Φ0.105 Φ0.205 Φ0.255 Φ0.305 | Common | K. M. N. L series Manual type 330A Power supply |
|  | F108 | A290-8011-X753 A290-8011-X754 A290-8011-X755 | Φ0.205 Φ0.255 Φ0.305 | Common | K. M. N. L series Manual type 60A Power supply |
|  | F110 | A290-8101-X730 A290-8101-X732 A290-8101-X733 A290-8101-X734 A290-8101-X735 | Φ0.105 Φ0.155 Φ0.205 Φ0.255 Φ0.305 | Upper | α-A. B. C. iA. iB series Manual type |
|  | F111 | A290-8101-X740 A290-8101-X742 A290-8101-X743 A290-8101-X744 A290-8101-X745 | Φ0.105 Φ0.155 Φ0.205 Φ0.255 Φ0.305 | Lower | α-A. B. C. iA. iB series Manual type |
|  | F112 | A290-8092-X702 A290-8092-X704 A290-8092-X705 A290-8092-X706 A290-8092-X707 | Φ0.105 Φ0.155 Φ0.205 Φ0.255 Φ0.305 | Upper | α-A. B. C. iA. iB series AWF type |

Fanuc

Wire Guide

| Picture | Code No. | Original P/No. | Dimension | Position | Application |
|---|--------------|--|--|----------|---|
|  | F112T | A290-8112-Z725 A290-8112-Z705 A290-8112-Z726 A290-8112-Z706 | Φ0.205 Φ0.205 Φ0.255 Φ0.255 | Upper | α-A. B. C. iA. iB. iC series AWF type Taper 30°~45° |
|  | F113 | A290-8092-X712 A290-8092-X714 A290-8092-X715 A290-8092-X716 A290-8092-X717 | Φ0.105 Φ0.155 Φ0.205 Φ0.255 Φ0.305 | Lower | α-A. B. C. iA. iB series AWF type Replaced by A290-8110-X712~717 |
|  | F113T | A290-8112-Z735 A290-8112-Z715 A290-8112-Z736 A290-8112-Z716 | Φ0.205 Φ0.205 Φ0.255 Φ0.255 | Lower | α-A. B. C. iA. iB. iC series AWF type Taper 30°~45° |
|  | F114 | A290-8104-Y714 A290-8104-Y715 A290-8104-Y716 A290-8104-Y717 | Φ0.155 Φ0.205 Φ0.255 Φ0.305 | Upper | α-A. B. C. iA. iB. iC. iD. iE series AWF type High accuracy type |
|  | F114A | A290-8104-Y704 A290-8104-Y705 A290-8104-Y706 A290-8104-Y707 | Φ0.152 Φ0.202 Φ0.252 Φ0.302 | Upper | α-A. B. C. iA. iB. iC. iD. iE series AWF type High accuracy type |
|  | F114B | A290-8114-Z725 A290-8114-Z726 | Φ0.205 Φ0.255 | Upper | α-A. B. C. iA. iB. iC. iD. iE series AWF type / For taper 30° |
|  | F114C | A290-8112-Z705 A290-8112-Z706 | Φ0.205 Φ0.255 | Upper | α-A. B. C. iA. iB. iC. iD. iE series AWF type / For taper 45° |
|  | F115 | A290-8119-Y714 A290-8119-Y715 A290-8119-Y716 A290-8119-Y717 | Φ0.155 Φ0.205 Φ0.255 Φ0.305 | Lower | α-A. B. C. iA. iB. iC. iD. iE series AWF type High accuracy type |
|  | F115A | A290-8119-Y704 A290-8119-Y705 A290-8119-Y706 A290-8119-Y707 | Φ0.152 Φ0.202 Φ0.252 Φ0.302 | Lower | α-A. B. C. iA. iB. iC. iD. iE series AWF type High accuracy type |
|  | F115B | A290-8114-Z735 A290-8114-Z736 | Φ0.210 Φ0.260 | Lower | α-A. B. C. iA. iB. iC. iD. iE series AWF type / For taper 30° |
|  | F115C | A290-8112-Z715 A290-8112-Z716 | Φ0.210 Φ0.260 | Lower | α-A. B. C. iA. iB. iC. iD. iE series AWF type / For taper 45° |
|  | F120A | A290-8110-Y726 | Φ1.0 | Upper | α-A. B. C. iA. iB series AWF type / Sub guide / 2-flat cut on flange Φ23.2 - 2Cut of 22.1 |




Fanuc

Wire Guide

| Picture | Code No. | Original P/No. | Dimension | Position | Application |
|---|---------------|--|--------------------------------------|----------|--|
|  | F120B | A290-8109-X753 | Φ1.0 | Upper | α-A. B. C. iA. iB series AWF type / Sub guide / 3-flat cut on flange Φ23.2 - 2Cut of 22.1 & 1Cut of 21 |
|  | F120C | A290-8109-X753 | Φ1.0 | Upper | α-A. B. C. iA. iB series AWF type / Sub guide 4-flat cut on flange |
|  | F121 | A290-8110-Y774 | Φ1.0 | Lower | α-A. B. C. iA. iB series AWF type / Sub guide Replaced by F124 |
|  | F122 | A290-8101-X753 | Φ0.35 | Upper | α-A. B. C. iA. iB series AWF type / Sub guide |
|  | F123 | A290-8037-X645 | Φ0.40 | Upper | W-series Sub die guide |
|  | F124A | A290-8110-Y774 | Φ11xΦ1.0 | Lower | α-A. B. C. iA. iB series AWF type / Sub die guide Full ceramic - Flange OD 11mm |
|  | F124B | A290-8110-Y774 | Φ12xΦ1.0 | Lower | α-A. B. C. iA. iB series AWF type / Sub die guide Full ceramic - Flange OD 12mm |
|  | F125 | A290-8102-Y754 A290-8102-Y755 A290-8102-Y756 A290-8102-Y757 A290-8102-Y761 | Φ1.8 Φ0.8 Φ1.5 Φ0.5 Φ1.0 | Upper | α-A. B. C. iA. iB series Jet nozzle Stainless housing+Ceramic insert |
|  | F126 | A290-8102-X723 | Φ58x19T | Upper | α-A. B series AWF type Nozzle base with 4 side hole |
|  | F127 | A290-8110-Y723 | Φ58x19T | Upper | α-C, iA. series AWF type Nozzle base with 5 side hole |
|  | F128A | A290-8104-X620 A290-8102-X620 | Φ0.35 Φ0.55 | Upper | α-A. B. C. iA. iB series Sub guide OD10 x ID0.3-0.5 x 14mm |
|  | F129 | A97L-0201-0490 | Φ1.5 | | α-A. B. C. iA. iB series Jet nozzle Stainless housing+Ceramic insert |
|  | F129-1 | A27L-0201-0490 | #80 - Φ1.5 #136 - Φ2.0 | | α-iA series Jet nozzle Stainless housing+Ceramic insert |

Fanuc

Wire Guide

| Picture | Code No. | Original P/No. | Dimension | Position | Application |
|---|-------------|----------------|-----------|----------|---|
|  | F130 | A290-8102-X764 | | | α-A. B. C. iA. iB series AWF type / Nozzle Φ11/6xΦ2x13H |
|  | F140 | A290-8021-Y701 | Φ12xΦ6x8H | Upper | α-A. B. C. iA. iB series V-Ditch sapphire guide |
|  | F144 | | | Nozzle | Ceramic nozzle |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |